

Model: PFS531TW

Features:

Submersible sewage and effluent applications.

- **DISCHARGE:** 2" NPT, Female, Vertical
- **LIQUID TEMPERATURE:** 77°F Continuous, 104°F maximum
- **MOTOR HOUSING/ VOLUTE:** Cast Iron, Class 30
- **IMPELLER:** Recessed vortex, open vane, Cast Iron, Class 30
- **SHAFT & HARDWARE:** Stainless steel
- **PAINT:** Industrial grade powder coating
- **O-RINGS:** Buna-N
- **SEAL:** Single mechanical, Carbon/Ceramic/Buna-N
- **UPPER BEARING:** Single row, ball, oil lubricated
- **LOWER BEARING:** Single row, ball, oil lubricated
- **POWER CORD:** 20FT., SJTW, 16/3 Cord with plug, Pressure Grommet for Sealing and Strain Relief.
- **MOTOR:** Class B Insulation, Oil Filled, Squirrel Cage Induction
- **SINGLE PHASE:** Permanent Split Capacitor (PSC), Includes overload protection in motor
- **WARRANTY:** 2 year

 **WARNING:** CANCER AND REPRODUCTIVE HARM-
WWW.P65WARNINGS.CA.GOV



**Submersible Sewage
2" Discharge,
2" Spherical Solids
Manual Operation**

MODEL	HP	VOLTS	PHASE	HZ	RPM	FULL LOAD AMPS	LOCKED ROTOR AMPS	CORD SIZE	CORD TYPE	CORD O.D.	Simplex Control	Duplex Control
PFS531TW	0.5	115	1	60	3450	10.0	26.0	16/3	SJTW	0.335	PF1000	PF2000

Remove Plug for use with Control Panel.



Power-Flo Pumps & Systems

a Power-Flo Technologies company

877-24PUMPS • fax: 516-812-6897 • www.powerflopumps.com

2" - Sewage Pumps - PFS, 1/2HP - 3450RPM - 60Hz

Model: PFS531TW

2" - Sewage Pumps - PFS, 1/2HP - 3450RPM - 60Hz

