

**Model: PFSLTB1313F10**

**Features:**

Simplex (one pump) sewage ejector systems are ideal for Under Sinks, Laundry Trays, Wet Bars, Dehumidifiers, Water Softeners and Air Conditioners. When the level in the basin rises to the pre-set ON level the pump will energize and evacuate the collected liquid waste. The packaged system includes the pump, float control, basin, basin cover, discharge pipe and discharge valve.

- **BASIN:** 13" Dia. x 13" Deep x 1/8" Wall thk. (7 U.S. Gallons)  
Translucent Blue Polyethylene Resin
- **INLET:** 1-1/2" Threaded Spin-Weld
- **BASIN COVER:** Roll Top Structural Foam with 1-1/2" Discharge, 1-1/2" Vent & Electrical grommets, 1/8" Closed Cell Cover Gasket
- **DISCHARGE PIPE:** 1-1/2" x 14" Lg., Sch40 PVC with Air Bleed Hole
- **PIPE FITTING:** 1-1/2" Male Adapter, Sch40 PVC
- **DISCHARGE VALVE:** 1-1/4" x 1-1/2" Combination Full Flow Rubber Sleeve Check Valve
- **HARDWARE:** Stainless Steel
- **SEWAGE PUMP:** PFSPCPC5030721F10 - 1/2HP, 115 Volt, 1Phase, 3450RPM, Cast Iron, Vertical, Mechatronic Float, Normally Open (N/O), Reinforced thermoplastic, 10 Ft. cord w/Piggy-back plug, On point - 8.8", Off point - 4.4"
- **WARRANTY:** 3 year

 **WARNING:** CANCER AND REPRODUCTIVE HARM-  
WWW.P65WARNINGS.CA.GOV



**Pre-Assembled Simplex Under Sink Package  
1-1/2" Discharge, Vent and Inlet**

HEAD in Ft	0 Ft	5 Ft	10 Ft	15 Ft	20 Ft	25 Ft	Max Lift	Max Pressure
FLOW Gal/Min	72	65	58	52	42	28	30 Ft	13.2 psi
FLOW Gal/Hr	4300	3900	3500	3100	2500	1700		

PACKAGE MODEL	BASIN INLET	BASIN COVER	PUMP MODEL	HP	Volts/Ph	FL AMPS	Cord Length	Unit Wt.
PFSLTB1313F10	1-1/2"	One Piece	PFSPCPC5030721F10	1/2	115/1	4.7	10 ft	30 lbs



**Power-Flo Pumps & Systems**

*a Power-Flo Technologies company*

877-24PUMPS • fax: 516-812-6897 • www.powerflopumps.com

**Pre-Assembled Under Sink Package - 1/2HP - 115V - Cast Iron**

Sect. SU  
Page 6.1  
Rev. 02/2021

**Pre-Assembled Under Sink Package - 1/2HP - 115V - Cast Iron**

**Model: PFSLTB1313F10**

